

# Master Breeze™

## PEDESTAL FANS

24" and 30" Industrial Grade Fans and Accessories



*Typical AMB  
Pedestal Fan  
and Base  
shown  
(see back side for  
mounting options)*



Triangle's pedestal fans have a superior design and proven performance that provide powerful, convenient air circulation wherever its needed.

### *Master Breeze Features...*

- 115V, 60Hz, 1 phase motors with thermal overload protection
- OSHA compliant chrome plated fan guards
- Easy to assemble
- Heavy duty 12' power cord with molded grounded plug
- 30" diam. steel base for maximum stability
- Optional mounting accessories and wheel kits are available
- Balanced 3-paddle aluminum blade assembly
- Oscillating feature available
- Telescoping adjustable pole provides heights from 4'4" to 7'4"
- 2 and 3 speeds available, providing air movement from 5,600 to 9,600 cfm



### **TRIANGLE ENGINEERING OF ARKANSAS, INC.**

E-mail: [mail@trianglefans.com](mailto:mail@trianglefans.com) • Website: [www.trianglefans.com](http://www.trianglefans.com)

1101 North Redmond Rd. • Jacksonville, AR 72076  
(501) 982-7558 • Fax (501) 982-5691

**1-800-255-9014**




# PEDESTAL FANS

With Wall/Column Mounting Bracket, Suspension Bracket or Hanger Bracket and Optional Wheel Kit



WC

Triangle's adjustable fan head assembly can be used with the **Wall/Column Mounting Bracket**. This bracket allows the fan to be easily and securely mounted to a beam, column or any other flat surface. The extended head assembly permits the fan to be tilted or turned to direct the air flow in the desired



S

direction. The wall/column bracket has a powder coat finish. Mounting bolts are not included.

The **Suspension Bracket** allows fan head to be suspended from any 2"x beam or joist. Bracket has a galvanized finish, mounting bolts not included. This bracket **CAN NOT** be used with an oscillating head.



HB

The **Hanger Bracket** is for use with an oscillating head. Bracket has a durable, powder coat finish. Mounting bolts not included.

The optional **Wheel Kit** is simple to install and makes any pedestal fan easily portable.



WK

## WW 3030 Pedestal Fan

- Commercial Grade
- 3 Speeds
- Limited 1-year warranty



Model No.	Blade Diameter	CFM Hi/Lo	Motor HP	Amps	Shipping Weight
AMB 2421 H	24"	6,100/4,300	1/4	2.6	42
AMB 2431 H OC	24"	6,000/4,000/3,000	1/4	2.7	47
AMB 2423 H	24"	7,800/5,300	1/2	6.2	42
AMB 3021 H	30"	7,200/5,400	1/4	2.6	49
AMB 3031 H OC	30"	7,100/5,100/3,100	1/4	2.7	54
AMB 3023 H	30"	8,800/6,400	1/2	6.2	49
AMB 2421 WC	24"	6,100/4,300	1/4	2.6	48
AMB 2431 WC OC	24"	6,000/4,000/3,000	1/4	2.7	53
AMB 2423 WC	24"	7,800/5,300	1/2	6.2	49
AMB 3021 WC	30"	7,200/5,400	1/4	2.6	48
AMB 3031 WC OC	30"	7,100/5,100/3,100	1/4	2.7	53
AMB 3023 WC	30"	8,800/6,400	1/2	6.2	49
AMB 2421 S	24"	6,100/4,300	1/4	2.6	50
AMB 2423 S	24"	7,800/5,300	1/2	6.2	50
AMB 3021 S	30"	7,200/5,400	1/4	2.6	54
AMB 3023 S	30"	8,800/6,400	1/2	6.2	54
AMB 2431 HB OC	24"	6,000/4,000/3,000	1/4	2.7	58
AMB 3031 HB OC	30"	7,100/5,100/3,100	1/4	2.7	59
AMB 2421	24"	6,100/4,300	1/4	2.6	80
AMB 2431 OC	24"	6,000/4,000/3,000	1/4	2.7	85
AMB 2423	24"	7,800/5,300	1/2	6.2	80
AMB 3021	30"	7,200/5,400	1/4	2.6	83
AMB 3031 OC	30"	7,100/5,100/3,100	1/4	2.7	88
AMB 3023	30"	8,800/6,400	1/2	6.2	83
WW 3030	30"	3,800/3,500/3,000	1/5	3.0	68
WK 2430 Wheel Kit					15

H = Head only  
 WC = Wall/Column mounting bracket supplied in place of pedestal and base  
 S = Suspension bracket supplied in place of pedestal and base  
 HB = Hanger Bracket for Oscillating fan only  
 OC = Three-speed oscillator motor. Standard RPM on high speed is 1100

All fan motors are 115 Volts • AMB carton size: 36½" x 14½" x 43½" • WW 3030 carton size: 34" x 9" x 40½"