

# Shutter Mounted Direct Drive Exhaust Fans

## Features

- Can be installed from inside wall
- Eliminates need for external framing and shutter
- Pull chain switch
- No Cord-Junction box provided for direct wiring
- Aluminum blade
- Steel spiral wire guards

## Motor Specifications

- 120V, 1 phase, totally enclosed, permanently lubricated
- 1/12 HP motor is 3-Speed sleeve bearing permanent split capacitor
- 1/8 HP motor is 3-Speed sleeve bearing permanent split capacitor
- 1/4 HP motor is 2-Speed ball bearing permanent split capacitor

Note: Rough-in hole size is 1/2" inch larger than fan blade size



## Standard Models

FAN SIZE	UPC# 686334	MODEL	HP	CFM / RPM			AMPS HIGH	WT. (LBS)
				HIGH	MED	LOW		
10"	868990	CE 10-DS	1/12	680 / 1560	540 / 1250	460 / 1080	1	11
12"	798624	CE 12-DS	1/12	825 / 1560	710 / 1250	560 / 1080	1.1	16
14"	869003	CE 14-DS	1/8	1520 / 1660	1400 / 1550	1250 / 1370	2	17
16"	869010	CE 16-DS	1/8	2100 / 1660	1900 / 1550	1700 / 1370	2.1	18
18"	798631	CE 18-DS	1/8	2300 / 1660	2100 / 1050	1850 / 1370	2.2	25
20"	869027	CE 20-DS	1/4	2925 / 1140	-	2380 / 1070	2.3	34
24"	798648	CE 24-DS	1/4	3400 / 1140	-	2770 / 1070	2.5	47
30"	798655	CE 30-DS	1/4	3950 / 1140	-	3080 / 1070	2.7	54

## Dimensions (Inches)

SIZE	DEPTH	DIMENSIONS		
		"A"	"B"	"C"
10"	5.81"	13.125"	10"	12.375"
12"	7.18"	15.125"	12"	14.375"
14"	7.18"	17.125"	14"	16.375"
16"	7.18"	19.125"	16"	18.250"
18"	7.18"	21.125"	18"	21.750"
20"	7.18"	23.125"	20"	23.686"
24"	7.18"	27.125"	24"	27.750"
30"	7.18"	33.125"	30"	33.750"

